




Ref.	Dimensions (mm)
Flange	F10 - F12
C x depth	M10x15
D x depth	M12x18
E	102
F	125
B	27
O	29.5
A	387.7
G	19
H (bore)	57.4
I	19
L	164.9
M	72.9
N	92
P	62
Q	72.9
R	29
S	30
T	134.9
W	1/4" GAS
Ch	27
Ancillaries Attachment	AA2

Double Acting Actuators - Output Torque related to rotation angle , in Nm (0°valve closed 90°valve open)

ROTATION ANGLE	Air pressure supply in bar							
	2,5	3	4	5	5,6	6	7	8
0°	214.3	257.1	342.9	428.6	480	514.3	600	685.7
50°	107.1	128.6	171.4	214.3	240	257.1	300	342.9
90°	160.7	192.9	257.1	321.4	360	385.7	450	514.3

Technical Data

Max Pressure	** Min Pressure	Rotation	Stroke Adjustment	Screw Stroke Adjustment	*Moving time (sec.)		Operating temperature (°C)
					Opening	Closing	
8.4 bar	1 bar	92° -1° +91°	10 °	For 1° drive Need 1/2 turn screw	0.46	0.4	Standard -20°C +80°C High temperature -20°C +150°C Low temperature -50°C +60°C

Weight Kg	Chamber Ø (mm)	Air volume L/cycle	Maximum flange torque values
9.6	100	2.45	F10 = 500 Nm F12 = 1000 Nm

****Attention:**
for "High Temperature"
and "Low Temperature" version,
the Min Pressure is 3 bar.

*The moving time could vary on different operating and installation factors .

Operating Medium

The operating medium shall have a dew point equal to - 20 °C or, to be at least, 10 °C below the ambient temperature (ISO 8573-1, Class 3).
The maximum particle size shall not exceed 40 µm (ISO 8573-1, Class 5).