



Ref.	Dimensions (mm)
<b>Flange</b>	F14
<b>D x depth</b>	M16x24
<b>F</b>	140
<b>B</b>	36
<b>O</b>	38.5
<b>A</b>	567
<b>G</b>	19.5
<b>H (bore)</b>	86.5
<b>I</b>	27
<b>L</b>	216
<b>M</b>	101.5
<b>N</b>	114.5
<b>P</b>	84.5
<b>Q</b>	101.5
<b>R</b>	41
<b>S</b>	30
<b>T</b>	186
<b>W</b>	1/4" GAS
<b>Ch</b>	36
<b>Ancillaries Attachment</b>	AA2

**Double Acting Actuators - Output Torque related to rotation angle , in Nm  
( 0°valve closed 90°valve open )**

ROTATION ANGLE	Air pressure supply in bar							
	2,5	3	4	5	5,6	6	7	8
0°	642.9	771.4	1028.6	1285.7	1440.0	1542.9	1800.0	2057.1
50°	321.4	385.7	514.3	642.9	720.0	771.4	900.0	1028.6
90°	482.1	578.6	771.4	964.3	1080.0	1157.1	1350.0	1542.9

**Technical Data**

Max Pressure	** Min Pressure	Rotation	Stroke Adjustment	Screw Stroke Adjustment	*Moving time (sec.)		Operating temperature (°C)
					Opening	Closing	
8.4 bar	1 bar	92° -1° +91°	10 °	For 1° drive Need 2/3 turn screw	2.3	2.4	Standard -20°C +80°C High temperature -20°C +150°C Low temperature -50°C +60°C

Weight Kg	Chamber Ø (mm)	Air volume L/cycle	Maximum flange torque values
23.4	145	7.6	F14 = 2000 Nm

**\*\*Attention:**  
for "High Temperature"  
and "Low Temperature" version,  
the Min Pressure is 3 bar.

\*The moving time could vary on different operating and installation factors .

**Operating Medium**

The operating medium shall have a dew point equal to - 20 °C or, to be at least, 10 °C below the ambient temperature (ISO 8573-1, Class 3).  
The maximum particle size shall not exceed 40 µm (ISO 8573-1, Class 5).